



REAR ELEVATION, NTS

**KEY**

Stone Plinth Wall: Steam clean granite using Doff system or similar (Do not use abrasive cleaning methods). Remove any vegetation by hand. Rake loose or cement-based pointing and repoint joints with sand and lime mortar: NHL 3.5. New pointing mortar to be recessed by 5mm from face of stonework.

Ironwork: Remove loose rust, prime and paint ironwork.

NOTES:  
 ALL DIMENSIONS TO BE CHECKED ON SITE.  
 DO NOT SCALE FROM DRAWING.  
 DISCREPANCIES AND OMISSIONS TO BE REPORTED IMMEDIATELY TO CARRIG CONSERVATION INTERNATIONAL.  
 THIS DRAWING IS COPYRIGHT AND IS ISSUED ON THE CONDITION THAT IT IS NOT COPIED EITHER WHOLLY OR IN PART WITHOUT THE CONSENT IN WRITING OF CARRIG CONSERVATION INTERNATIONAL

**CARRIG**  
 conservation international

Second Floor - Atlantis Building South Cumberland Street phone: 01 353 1 5529080 e-mail: info@carrig.ie www.carrig.ie <small>DRAWING COPYRIGHT - CARRIG CONSERVATION INTERNATIONAL</small>	
CLIENT	Carr Cotter & Naessens Architects
PROJECT TITLE	Carlow Library
DRAWING TITLE	Proposed Railing Refurbishment
DRAWING STATUS	External Recommendations Drawings

DATE	SCALE	PROJECT NUMBER	DESIGN NUMBER	REVISION
PT	SH	30.11.2020	NTS@A3	R00
		020024	R06	